

SQUIRE®

Lock makers since 1780

1.



Lockset locked to provide maximum protection.

3.



To allow access, the door is required to swing towards you before the hasp can swing down

2.



Remove lock body to reveal steel locking stud.

4.



When access is required the lock body should be secured on the locking stud to prevent its loss.

Customer Helpline: 01902 308052 (8am - 5pm Monday - Friday)

SQUIRE®

Lock makers since 1780

1.



Lockset locked to provide maximum protection.

3.



To allow access, the door is required to swing towards you before the hasp can swing down

2.



Remove lock body to reveal steel locking stud.

4.



When access is required the lock body should be secured on the locking stud to prevent its loss.

Customer Helpline: 01902 308052 (8am - 5pm Monday - Friday)

SQUIRE®

Lock makers since 1780

1.



Lockset locked to provide maximum protection.

3.



To allow access, the door is required to swing towards you before the hasp can swing down

2.



Remove lock body to reveal steel locking stud.

4.



When access is required the lock body should be secured on the locking stud to prevent its loss.

Customer Helpline: 01902 308052 (8am - 5pm Monday - Friday)

SQUIRE®


Lock makers since 1780

1.



Lockset locked to provide maximum protection.

3.



To allow access, the door is required to swing towards you before the hasp can swing down

2.



Remove lock body to reveal steel locking stud.

4.



When access is required the lock body should be secured on the locking stud to prevent its loss.

Customer Helpline: 01902 308052 (8am - 5pm Monday - Friday)

SQUIRE®

Lock makers since 1780

1.



Lockset locked to provide maximum protection.

3.



To allow access, the door is required to swing towards you before the hasp can swing down

2.



Remove lock body to reveal steel locking stud.

4.



When access is required the lock body should be secured on the locking stud to prevent its loss.

Customer Helpline: 01902 308052 (8am - 5pm Monday - Friday)

SQUIRE®

Lock makers since 1780

1.



Lockset locked to provide maximum protection.

3.



To allow access, the door is required to swing towards you before the hasp can swing down

2.



Remove lock body to reveal steel locking stud.

4.



When access is required the lock body should be secured on the locking stud to prevent its loss.

Customer Helpline: 01902 308052 (8am - 5pm Monday - Friday)